



## 技术参数

规格型号	CDT10KL-S		CDT15KL-S		CDT20KL-S		
相位	三进单出						
容量	10000 VA/8000 W		15000 VA/12000 W		20000 VA/16000 W		
<b>输入</b>							
电压范围	低电压转换	176 VAC (同相电压) $\pm$ 3% @ 100%负载; 110 VAC (同相电压) $\pm$ 3% @ 50% 负载					
	低电压恢复	186 VAC (同相电压) $\pm$ 3% @ 100%负载; 120 VAC (同相电压) $\pm$ 3% @ 50% 负载					
	高电压转换	300 VAC (同相电压) $\pm$ 3%					
	高电压恢复	290VAC (同相电压) $\pm$ 3%					
频率范围	46-54 Hz 或 56-64Hz						
功率因数	$\geq$ 0.99 @ 100% 负载						
<b>输出</b>							
输出电压	208/220/230/240VAC			208/220/230/240VAC			
电压范围 (电池模式)	$\pm$ 1%						
频率范围 (同步校正范围)	46-54Hz 或 56-64Hz						
频率范围 (电池模式)	50 Hz $\pm$ 0.1 Hz 或 60 Hz $\pm$ 0.1 Hz						
浪涌比率	3:1						
谐波失真	$\leq$ 3% THD (阻性负载) $\leq$ 5% THD (非线性负载)						
转换时间	旁路至逆变	0					
	逆变至旁路	0					
波形 (电池模式)	纯正弦波						
<b>效率</b>							
市电模式	91%		91%		91%		
电池模式	91%		91%		91%		
<b>电池</b>							
	电池型号	12V / 9Ah					